

Safety Data Sheet

Section 1 - Chemical Product and Company Information

Product Name: Blended Silicate Solution Product Code: SCF-Base Boost

Trade Name: Base Boost

Manufactured by: Chemtrec

Smith Paint Products
2900 Fairview Park Drive
2200 Paxton Street
Falls Church, VA 22042-4513
Harrisburg, PA 17111
(800) 262-8200

Emergency Hot Line: (800) 424-9300

Product Use: Additive to primer for the primary or base color of Smith's Color Floor or Color Wall installation Not recommended for: Application to overlay systems, previously coated substrates or use in highlight colors.

Section 2 - Hazards Identification

GHS Ratings:

(800) 466-8781

Skin corrosive 2 Reversible adverse effects in dermal tissue, Draize score: >=

2.3 < 4.0 or persistent inflammation

Eye corrosive 2A Eye irritant: Subcategory 2A, Reversible in 21 days

GHS Hazards

H315 Causes skin irritation

H319 Causes serious eye irritation

GHS Precautions

P264 Wash ... thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P321 Specific treatment (see ... on this label)

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with soap and water

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P332+P313 If skin irritation occurs: Get medical advice/attention P337+P313 If eye irritation persists, get medical advice/attention

Signal Word: Warning



SDS for: SCF-Base Boost Page 1 of 5

Printed: 10/7/2015 at 11:10:11AM

Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Water softened	7732-18-5	90.00% - 100.00%
SILCIC ACID POTASSIUM SILICATE	1312-76-1	5.00% - 10.00%
SILICIC ACID LITHIUM SILICATE	12627-14-4	1.00% - 5.00%

Section 4 - First Aid Measures

INHALATION: Move victim to fres air at once. If breathing has stopped, perform artificial respiration. Get medical attention as soon as possible.

EYE CONTACT: Flush eyes with plenty water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Remove contaminated clothing. Wash off quickly with plenty of water, then soap and water. For sever exposure shower and get medical attention.

INGESTION: If swallowed, dilute with 2 to 4 glasses of water. Do not induce vommiting, obtain medical treatment immediately. Never give anything by mouthto an unconscious person.

Section 5 - Fire Fighting Measures

Flash Point: N/A

LEL: UEL:

Flammable Limits:

Extinguishing Media: This product is compatible with all extinguishing media.

Unusual Hazards: Spilled material is very slippery. This material dries to form glass, a film which can easily cut

skin.

Haz. Comb. Products: THis product is non combustible.

Fire Fighting Equipment: Chemical goggles, body-covering protective clothing, chemical resistant gloves and rubber boots.

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE). Spills may be very slippery when wet, use caution during cleanup.

Section 7 - Handling and Storage

Handling Precautions: Wear all appropriate Personal Protective Equipment (PPE). Wear body covering protective clothing gloves. Use NIOSH approved dust and mist respirator where spray mist occurs. Abserve OSHA regulations for respirator use (29 C.F.R. 1910.134) and wear chemical splash goggles.

STORAGE: Prevent from freezing. Do not store above 90 F (40 C).

Store only in original containers.

Section 8 - Exposure Controls / Personal Protection

SDS for: SCF-Base Boost Page 2 of 5

Water softened 7732-18-5	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established
SILCIC ACID POTASSIUM SILICATE 1312-76-1	Not Established	Not Established	Not Established
SILICIC ACID LITHIUM SILICATE 12627-14-4	Not Established	Not Established	Not Established

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Evaporation rate: Not Determined

Appearance: Clear Liquid Odor: Low Odor

Vapor Pressure: N/AOdor threshold: Not DeterminedVapor Density: 0.6pH: Not Determined

Specific Density: 1.06Melting point: Not DeterminedFreezing point: 0°CSolubility: Not DeterminedBoiling range: 100°CFlash point: 999 F,999 C

Explosive Limits: 0% Partition coefficient (n- Not Determined

octanol/water):

Autoignition temperature: N/A Decomposition temperature: Not Determined

Viscosity: 1 cPs Grams VOC less water: 90.35

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibilities/Condictions to avoid: Gels and generates heat when mixed with acid. Absorbs carbon monoxide when exposed to air. May react with ammonium salts resulting in evolution of ammonium gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.

Hazardous Decomposition: Not applicable. Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Component Toxicity

Primary routes of entry: Skin contact.

SDS for: SCF-Base Boost Page 3 of 5

Flammability: Not Determined

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS NumberDescription% WeightCarcinogen RatingNoneNo Data Available

Section 12 - Ecological Information

Component Ecotoxicity

Water softened Toxicity of the Products of Biodegradation: The product itself and its products of

degradation are not toxic.

SILICIC ACID LITHIUM SILICATE Toxicity Lithium compounds - no data.

Persistence and degradability: Inorganic. Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved

silica.

Bioaccumulative potential: Inorganic. The substance has no potential for

bioaccumulation.

Mobility in soil: Not applicable.

Results of PBT and vPvB assessment: Not classified as PBT or vPvB.

Other adverse effects: The alkalinity of this material will have a local effect on

ecosystems sensitive to changes in pH.

Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

AgencyProper Shipping NameUN NumberPacking GroupHazard ClassDOTPaint - Silicate SolutionUnregulatedNot Regulated

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

R2K List

- None

Section 16 - Other Information

SDS for: SCF-Base Boost Page 4 of 5

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend


* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH



The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Reviewer Revision

Date Prepared: 10/7/2015

SDS for: SCF-Base Boost Page 5 of 5