



# OIL CLEAN

**GENERAL PROPERTIES:** a powerful solution for cleaning problematic oil stains left by vehicles and equipment. Smith's Oil Clean effectively removes oil stains on concrete and other hard surfaces, while an enzymatic cleaning process removes residual oil stains by degrading a wide variety of hydrocarbon compounds. Continued use prevents future soil buildup, maintaining surfaces that are clean.

- Easy to use
- Concentrated – dilute with potable water
- Superior Performance
- Solvent free
- Overnight deliverable

**RECOMMENDED USE:** Cleaning difficult oil stains from concrete; scheduled maintenance program for cleaning hard surfaces

**COLOR:** clear/tan liquid

**COVERAGE PER “READY TO USE” GALLON:**

50-200 square feet - Coverage depends on surface profile and stain saturation

**STORAGE CONDITIONS:**

Temperature: 40-90°F

**VOLATILE ORGANIC CONTENT:**

**SHELF LIFE:**

Unopened Container 1 year

**ORDERING INFORMATION**

Prices may be obtained from Smith Paint Products, Sales Representative or local Smith's Decorative Concrete Products Dealer.

**APPLICATION INSTRUCTIONS**

Remove paint, adhesives and loose particulates from the intended cleaning area. It is best to apply Smith's Oil Clean to intended area at night, allowing product to dwell undisturbed for as long as possible. Smith's Oil Clean must be kept damp to remain active. For high temperature application or areas exposed to excess winds, apply plastic sheeting over treated area.

**Heavily Stained Substrates:**

- 1) Liberally apply Smith's Oil Clean at full strength.
- 2) Allow product to dwell on the substrate for 20 minutes.

- 3) Agitate Smith's Oil Clean utilizing a floor buffer, stiff bristle broom or deck brush.
- 4) Rinse area with clean water.

**General Maintenance / lightly soiled areas:**

- 1) Diluted 1 part Smith's Oil Clean with 4 parts potable water (e.g. 8 oz. Smith's Oil Clean with 32 oz. of potable water)
- 1) Liberally apply Smith's Oil Clean let down solution to intended cleaning area via spray or pouring.
- 2) Allow product to dwell on the substrate for 20 minutes.
- 3) Agitate treated area utilizing a floor buffer, stiff bristle broom or deck brush.
- 4) Rinse area with clean water.

**CLEAN UP:**

Store material in a cool, dry place. Wash hands and tooling thoroughly with warm, soapy water after contact.

Upon information, belief and to the best of our knowledge, the information contained herein is true and accurate as of the date of issuance of this particular product and any and all information conveyed, expressed or implied is subject to change without prior notice. We guarantee our products to conform to Smith Paint Products' quality control mechanisms, but not to any other standards. We assume no responsibility for coverage, performance or injuries resulting from use, misuse or uses not described in any promotional materials. Promotional materials are not a supplementation to any contract or expand any term or condition of the product purchase agreement, if any is reduced to writing. Liability, if any, is limited to replacement of the purchased product upon presentation of valid sales receipt or invoice, and no damages for any consequential, liquidated or other damages are provided under this Limitation of Liability and Limited Warranty. NO OTHER WARRANTY OR GUARANTY OF ANY KIND IS MADE BY SMITH PAINT PRODUCTS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. DO NOT PURCHASE AND USE THIS PRODUCT IF YOU HAVE NOT AGREED TO THE ABOVE TERMS.

